


IG-52HGM

03 & 04 TYPE



外形尺寸/ Appearance Size



unit:mm

齒輪馬達轉矩 & 速度/ Geared Motor Torque & Speed

	減速比 Reduction ratio	1/4	1/13	1/15	1/19	1/46	1/57	1/67	1/82	1/98	1/114	1/161	1/207	1/288	1/357	1/494	1/552	1/684			
	定額扭力 Rated torque (Kg-cm)	2.7	8	9.5	11	24	30	35	44	52	61	72	93	100	100	100	100	100			
12V	定額轉數 Rated speed (rpm)	960	275	235	190	78	63	54	44	37	31.7	22.5	17.4	12.7	10.5	7.6	6.7	5.5			
	定額扭力 Rated torque (Kg-cm)	3.9	11	13	17	35	44	51	64	76	88	100	100	100	100	100	100	100			
24V	定額轉數 Rated speed (rpm)	940	270	230	186	77	62	53	43	36	31.1	22	17.3	12.7	10.5	7.6	6.7	5.5			
	軸心迴轉方向 Rotation direction	CW																			
長度 Length (L)		53.0		68.5		84.0						99.5									

馬達單體型式/ Motor Data

定額電壓 Rated volt (V)	定額扭力 Rated torque (g-cm)	定額轉數 Rated speed (rpm)	定額電流 Rated current (mA)	無負荷轉數 No load speed (rpm)	無負荷電流 No load current (mA)	定額出力 Rated output (W)	重量 Weight (g)
12	900	3620	≤ 4100	4000	≤ 1200	33.5	920
24	1300	3550	≤ 2850	4000	≤ 700	48.6	920

馬達單體特性/ Motor Characteristics

