


IG-62



外形尺寸 & 馬達裝卸方法/ Appearance Size & Motor Installation



產品規格/ Product Specifications

外殼材質 Housing material	輸出軸承型式 Bearing at output	徑向負荷 Radial load (10mm from flange)	軸向負荷 Shaft axial load	主軸最大承受壓入力 Shaft press fit force, max.	徑向間隙 Radial play of shaft	軸向間隙 Thrust play of shaft	背隙 (無負荷時) Backlash, at no-load
金屬 Metal	滾珠軸承 Ball bearings	$\leq 25 \text{ kgf}$	$\leq 10 \text{ kgf}$	$\leq 50 \text{ kgf}$	$\leq 0.08 \text{ mm}$	$\leq 0.4 \text{ mm}$	$\leq 3^\circ$

馬達齒輪型式/ Pinion Specifications

模數 Module	齒數 No. of teeth	壓力角 Pressure angle	孔徑 (mm) Hole diameter	減速比 Reduction ratio
1.0	12	20°	$\phi 6 \times 4.5$	1/4, 1/15, 1/19, 1/53, 1/66, 1/81, 1/113, 1/230 1/285, 1/353, 1/488, 1/546, 1/676
1.0	14	20°	$\phi 8 \times 6$	1/100
1.0	16	20°	$\phi 8 \times 6$	1/3, 1/12, 1/43, 1/150

標準減速比型式/ Gearboxes Specifications

減速比 Reduction ratio	1/3	1/4	1/12	1/15	1/19	1/43	1/53	1/66	1/81	1/100	1/113	1/150	1/230	1/285	1/353	1/488	1/546	1/676				
定格容許扭力 (kgf-cm Max.) Rated tolerance torque	15	15	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100				
瞬間容許扭力 (kgf-cm) Max momentary tolerance torque	45	45	150	150	150	300	300	300	300	300	300	300	300	300	300	300	300	300				
效率 Efficiency	80%	80%	70%	70%	70%	60%	60%	60%	60%	60%	60%	50%	50%	50%	50%	50%	50%	50%				
長度 Length (L)	43.6	43.6	59.1	59.1	59.1	74.6	74.6	74.6	74.6	74.6	74.6	90.1	90.1	90.1	90.1	90.1	90.1	90.1				
重量 (滾珠軸承) Weight (g) / Ball bearings	670	670	940	940	940	1220	1220	1220	1220	1220	1220	1500	1500	1500	1500	1500	1500	1500				

- 使用相對濕度：20%~85%RH
Operating relative humidity
- 使用溫度範圍：-10℃~+60℃
Operating temperature range