

HP-4P	GEAR RATIO	TYPE	A	D	E	F	G	H	J	K	L	M	X	Y	KG
100W 1/8HP	3-50	18	168	40	110	135	65	9	16	45	10	72.5	132	88.5	3
	60-200	22	200	65	130	160	90	11	18.2	56	15	80	152	97.5	4
200W 1/4HP	3-10	18	168	40	110	135	65	9	16	45	10	72.5	132	88.5	3
	15-90	22	200	65	130	160	90	11	18.2	56	15	80	152	97.5	5
	100-200	28	258	90	140	180	120	11	20.8	65	15	95.2	180	116	7
400W 1/2HP	3-10	22	207	65	130	160	90	11	18.2	56	15	80	152	97.5	6
	15-90	28	263	90	140	180	120	11	20.8	65	15	95.2	180	116	7
	100-200	32	300	130	170	215	160	13	30.2	76	25	108.5	210	138.5	12.6
750W 1HP	3-25	28	269	90	140	180	120	11	20.8	65	15	95.2	180	116	7
	30-120	32	310	130	170	215	160	13	30.2	76	25	108.5	210	138.5	14.6
	125-200	40	336	150	210	260	185	15	42.2	85	25	117.8	248	160	35
1500W 2HP	3-25	32	320	130	170	215	160	13	30.2	76	25	108.5	210	138.5	14.6
	30-120	40	350	150	210	260	185	15	42.2	85	25	117.8	248	160	35
2200W 3HP	3-60	40	360	150	210	260	185	15	42.2	85	25	117.8	248	160	35
	70-120	50	410	170	265	330	220	19	51.7	104	30	148.6	315	200	43
3700W 5HP	3-25	40	360	150	210	260	185	15	42.2	85	25	117.8	248	160	35
	30-80	50	410	170	265	330	220	19	51.7	104	30	148.6	315	200	43

INPUT BORE	SHAFT			KEYWAY			KEY
	KW	S1h6	P1	W1	T1	Q1	SPEC
0.1/0.2	14	25	5	16	22	5×5×22	
0.4	14	30	5	16	26	5×5×25	
0.75	19	40	6	21.5	35	6×6×35	
1.5	24	50	8	27	45	8×7×45	
2.2	28	60	8	31	50	8×7×50	
3.7	28	60	8	31	50	8×7×50	

OUTPUT SHAFT	SHAFT			KEYWAY			KEY
	Sh6	P	W	T	Q	SPEC	
Φ18	30	5	20	25	5×5×25		
Φ22	40	7	25	35	7×7×35		
Φ28	45	7	31	40	7×7×40		
Φ32	55	10	35.5	50	10×8×50		
Φ40	65	10	43.5	60	10×8×60		
Φ50	80	14	54	75	14×9×75		

